

LUBRICATION ORDER

LO 10 3930-607 12

22 February 84

(Supersedes LO 10-3930-607-12-1 and -2, 26 MAY 1969)

**TRUCK, LIFT, FORK; GASOLINE ENGINE DRIVEN,
SOLID RUBBER TIRES, 4,000 LB CAPACITY
(HYSTER MODEL S40CP, ARMY MODEL MHE-203)
(NSN 3930-00-935-7866) 100-INCH LIFT AND
(3930-00-935-7865) 180-INCH LIFT**

Reference: TM 10-3930-607-15 and FEDERAL SUPPLY CATALOG C9100-IL.

Hard time intervals and the related manhour times are based on normal operation. The man-hour time specified is the time you need to do all the services prescribed for a particular interval. Change the hard time interval if your lubricants are contaminated or if you are operating the equipment under adverse operating conditions, including longer-than-usual operating hours. The hard time interval may be extended during periods of low activity. If extended, adequate preservation precautions must be taken.

WARNING

Dry cleaning fluid is flammable. Do not use near a flame or excessive heat. Use only with adequate ventilation. Avoid prolonged breathing of vapors and minimize skin contact.

Clean parts or fittings with dry cleaning solvent (SD), Type II or equivalent. Dry before lubricating. Dotted arrow shafts indicate lubrication on both sides of equipment. A dotted circle indicates a drain below. Relubricate all items found contaminated after fording or washing.

The lowest level of maintenance authorized to lubricate a point is indicated by one of the following symbols as appropriate: Operator/Crew (C); and Organizational Maintenance (O).

Reporting errors and recommending improvements. You can help improve this manual. If you find any mistakes, or if you know of a way to improve the procedures, please let us know. Mail your letter or DA Form 2028 (Recommended Changes to Publications and Blank Forms) direct to: Commander, US Army Tank-Automotive Command, ATTN: DRSTA-MB, Warren, MI 48090. A reply will be furnished to you.

* The time specified is the time required to perform all services at the particular interval.

*TOTAL MAN-HOURS		*TOTAL MAN-HOURS	
INTERVAL	MAN-HOURS	INTERVAL	MAN-HOURS
10	0.3	500	0.5
50	0.1	1000	2.3
250	2.0		

TA220090

LO 10-3930-607-12

CARD 1 OF 6

LUBRICANT • INTERVAL

INTERVAL • LUBRICANT

Carriage Rollers
(Sealed bearings
no lubrication
required)

Brake Inching
Pedal Pivot
Points (0)

Drive Axle
Breather (0)
(Clean)

Drive Axle
Fill Plug (0)
(See Key)

Drive Axle
Level Plug (0)
(Check level)

Drive Axle
Drain Plug (0)
(Drain and refill)
(See Note 11)

GAA 250

250

GO

250

1000

250 BFS

Master Brake
Cylinder Fill
and Level (0)
(Check level)
(See Key)

1000 GAA

Wheel
Bearings (0)
(See Note 10)

250 GAA

Center Pin (0)
(Top and bottom)

250 GAA

Drag Link
Rear (0)

1000 GAA

Wheel
Bearings (0)
(See Note 10)

TA220091