

## LUBRICATION ORDER

30 MARCH1993

**L010-3930-660-12****TRUCK, FORKLIFT, 6000 LB.,  
VARIABLE REACH, ROUGH TERRAIN  
(NSN 3930-01-158-0849)**

Reference TM5-3930-660-20 and C9100-1 L

Intervals (on condition or hard time) and the related man-hour times are based on normal operation. The man-hour time specified is the time you need to do all the services prescribed for a particular interval. On-condition (OC) oil sample intervals shall be applied unless changed by the Army Oil Analysis Program (AOAP) laboratory. Change the hard time interval if your lubricants are contaminated or if you are operating the equipment under adverse operating conditions, including longer-than-usual operating hours. The hard time interval may be extended during periods of low activity. If extended, adequate preservation precautions must be taken. Hard time intervals will be applied in the event AOAP laboratory support is not available.

Clean fittings before lubricating. Clean parts with dry cleaning solvent (SD), type II or equivalent. Dry

before lubricating. Dotted arrow points indicate lubrication on both sides of the equipment. Level of maintenance. The lowest level of maintenance authorized to lubricate a point is indicated by one of the following symbols as appropriate: Operator/Crew(C); and Organizational Maintenance (O).

**REPORTING OF ERRORS**

Reporting errors and recommending improvements. You can help improve this manual. If you find any mistakes or if you know of a way to improve the procedures, please let us know. Mail your letter or DA Form 2028 (Recommended Changes to Publications and Blank forms) direct to: Commander, US Army Tank-Automotive Command, A IIN: AMSTA-MB, Warren, MI 48397-5000. A reply will be furnished to you.

## TOTAL MAN-HR

| INTERVAL | MAN-HR |
|----------|--------|
| 50       | 1.0    |
| 250      | 1.0    |
| 500      | 2.0    |
| 1000     | 2.0    |

Approved for public release; distribution is unlimited.

