

LUBRICATION
ORDER

2 JULY 1973 (Supersedes LO 5-2420-221-12-1 dated 22 JAN 71)

TRACTOR, WHEELED INDUSTRIAL; D E D 2 SINGLE FRONT WHEELS,

NON DRIVING STEERABLE; 2 SINGLE REAR WHEELS DRIVING,

NON-STEERABLE, W/15 CU FOOT FRONT END LOADER AND

22 INCH WIDE BACKHOE (J. I. CASE MODEL M48OCK)

W/ENGINE J. I. CASE MODEL 188

Reference: L05-2420-221-12-2 and FEDERAL SUPPLY CATALOG C9100-IL

Intervals are based on normal hours of operation. Adjust to compensate for abnormal operation and severe conditions. During inactive periods, sufficient lubrication must be performed for adequate preservation.

Clean parts with SOLVENT, dry-cleaning, or with OIL, fuel, Diesel. Dry before lubricating.

Lubricate points indicated by dotted arrow shaft on both sides of equipment.

Relubricate after washing.

Drain gearcase when hot. Fill and check level.

Clean fitting before lubricating.

*The time specified is the time required to perform all services at the particular interval.

* TOTAL MAN-HR		*TOTAL MAN-HR	
INTERVAL	MAN-HR	INTERVAL	MAN-HR
10	0.6	250	1.7
50	1.1	500	2.2
100	1.6	1000	3.1

FOLD

FOLD

INTERVAL ● LUBRICANT

LUBRICANT ● INTERVAL

