

LUBRICATION ORDER

LI-035238-10/1B

L05-2805-258-12

20 September 1989

[Supersedes LO 5-2805-258-12, 23 October 1978]

ENGINE, GASOLINE: 10 HP; MILITARY STANDARD MODELS

(MODEL 2A042-2, MODEL 2A042-3, AND MODEL 2A042-4)

Reference: TM 5-2805-258-14 and C9100-1L

Intervals and related task-hour times are based on normal hours of operation. The task-hour time specified is the time you need to do all the services prescribed for a particular interval. Change the interval if your lubricants are contaminated or if you are operating the equipment under adverse operating conditions, including longer-than-usual operating hours. You may extend the interval during periods of low activity, but you must take adequate preservation precautions.

*The time specified is the time required to perform all services at the particular interval.

Clean fittings before lubricating. Clean parts with

SOLVENT dry cleaning, or with OIL, fuel, diesel. Dry before lubricating. Drain crankcase when HOT. Fill and check level. The lowest level of maintenance authorized to lubricate a point is indicated by one of the following (C) Operator/crew; or (O) Organizational Maintenance.

You can help improve this publication. If you find any mistake or if you know of a way to improve the procedures, please let us know. Your letter or DA Form 2028 (Recommended Changes to Publications and Blank Forms) should be mailed directly to: Commander, U.S. Army Troop Support Command, ATTN: AMSTR-MCTS, 4300 Goodfellow Blvd. St. Louis, MO 63120-1798. A reply will be furnished to you.

*TOTAL TASK-HRS		*TOTAL TASK-HRS	
INTERVAL	TASK-HR	INTERVAL	TASK-HR
8	0.1		
50	0.5		

LUBRICANT • INTERVAL

INTERVAL • LUBRICANT

