

LUBRICATION

ORDER
LI-00664G-12

LO 5-4210-217-12

15 MAY 1975 (Supersedes L05-4210-217-12 dated 6 APRIL 1973)

TRUCK, FIRE FIGHTING: POWERED PUMPER; FOAM AND WATER 750 G.P.M. CAP.; CENTRIFUGAL PUMP, POWER TAKE OFF DRIVEN; 400 GAL. WATER TANK, 40 GAL. FOAM CHEMICAL TANK, (ENGINEERED DEVICES INC. MODEL 0814) FSN 4210-150-1426, (AMERICAN AIR FILTER MODEL FT 750) FSN 4210-106-7432 AND WINTERIZED (AMERICAN AIR FILTER MODEL FT 750W) FSN 4210-106-7433

Reference: TM5-4210-217-12, LO9-2320-209-12, and FEDERAL SUPPLY CATALOG C9100-IL

Intervals are based on normal hours of operation. Adjust to compensate for abnormal operations and severe conditions.

During inactive periods sufficient lubrication must be performed for adequate preservation.

Clean fittings before lubricating.

A dotted circle indicates a drain below.

Clean parts with SOLVENT, dry-cleaning, Type II (SD-2).

Dry before lubricating.

Lubricate points indicated by dotted arrow shafts on both sides of equipment.

* The times specified are the hours required to perform 311 services at the particular interval.

*TOTAL MAN-HR		* TOTAL MAN-HR	
INTERVAL	MAN-HR	INTERVAL	MAN-HR
50	1.0	250	1.1
100	1.5	500	1.1

LUBRICANT • INTERVAL

INTERVAL • LUBRICANT

