

DEPARTMENT OF THE ARMY TECHNICAL MANUAL

ORGANIZATIONAL MAINTENANCE REPAIR PARTS
AND SPECIAL TOOLS LISTS

GENERATOR SET, GAS TURBINE ENGINE:
45 KW, AC, 120/208 V, 240/416 V, 3 PHASE, 4 WIRE:
SKID MOUNTED: WINTERIZED (AIRESEARCH
MODEL GTGE 70 C 1)
FSN 6115-075-1639

This reprint includes all changes in effect the time of publication; change 2.
--

HEADQUARTERS, DEPARTMENT OF THE ARMY
OCTOBER 1968

TECHNICAL MANUAL

No. 5-6115-320-20P

HEADQUARTERS
DEPARTMENT OF THE ARMY
WASHINGTON, D. C., 24 October 1968

**ORGANIZATIONAL MAINTENANCE REPAIR PARTS
AND SPECIAL TOOLS LIST
GENERATOR SET, GAS TURBINE ENGINE: 45 KW, AC.,
120/208 V, 240/416 V, 3 PHASE, 4 WIRE: SKID MOUNTED:
WINTERIZED (AIRESEARCH MODEL GTGE 701)
FSN 6115-075-1639
Current as of 26 April 1968**

	Paragraph	Page
SECTION I. INTRODUCTION		
Scope	1	iii
General.....	2	iii
Explanation of columns.....	3	iii
Special information	4	v
How to locate repair parts	5	v
Abbreviations.....	6	v
Recommendations for maintenance manual improvements.....	7	v
Federal supply codes for manufacturers.....	8	vi
II. PRESCRIBED LOAD ALLOWANCE.....		vii
III. SPECIAL TOOLS, TEST AND SUPPORT EQUIPMENT FOR ORGANIZATIONAL MAINTENANCE (Not Applicable)		
IV. REPAIR PARTS FOR ORGANIZATIONAL MAINTENANCE		
Group 01. Engine		
0121 Compressor assembly (includes compressor and housing)		1
0122 Combustion assembly.....		1
0126 Fuel or steam control.....		2
0127 Lubricating system.....		6
06. Electrical System (Engine and Vehicular, etc.)		
0608 Starting motor		12
0605 Ignition components		12
0607 Instrument or engine control panel		13
0608 Miscellaneous items		14
0612 Batteries, storage (wet or dry)		14
0613 Hull or chassis wiring harness.....		16
18. Body, Cab, Hood and Hull		
1801 Body, cab, hood, hull assemblies		16
22. Body Chassis or Hull, and Accessory Items		
2201 Canvas, rubber, or plastic items		18
2207 Winterization equipment		18
2210 Data plates and instruction holders		20
40. Electric Motors and Generators		
4004 Ventilating system		22
4009 Control panels, housing, cubicles.....		22

*This manual superseded TM 5-6115-320-20P, 24 June 1966.

Group 40.	Electric Motors and Generators - Continued	
	4014 Resistors (fixed, variable or tapped)	24
	4018 Terminal blocks, junction boxes.....	24
42	Electrical Equipment	
	4213 Non rotating rectifiers, converters, inverters.....	25
47	Gages, (Non-Electrical Weighing and Measuring Devices	
	4702 Gages, mountings, lines, and fittings.....	26
Section V.	FEDERAL STOCK NUMBER AND REFERENCE NUMBER INDEX	57

SECTION I

INTRODUCTION

1. Scope

This manual lists repair parts and special tools required for the performance of organizational maintenance of the generator set.

2. General

a. The Repair Parts List is arranged as follows:

(1) Individual parts and major assemblies are listed alphabetically by item name within the numbered functional groups.

(2) Assembly components and subassemblies are indented and listed alphabetically by item name under major assemblies.

b. This Repair Parts and Special Tools List is divided into the following sections:

(1) *Prescribed Load Allowance (PLA)* Section II. A consolidated listing of repair parts quantitatively allocated for initial stockage at the organizational level. This is a mandatory stockage allowance.

(2) *Special Tools, Test and Support Equipment* Section III. A list of special tools, test and support equipment authorized for the performance of maintenance at the organizational level (Not Applicable).

(3) *Repair Parts* Section IV. A list of repair parts authorized for the performance of maintenance at the organizational level.

(4) *Federal Stock Number and Reference Number Index* Section V. A list of Federal stock numbers followed by reference numbers in ascending alpha-numeric sequence, cross-referenced to index number.

3. Explanation of Columns

The following provides an explanation of columns in the tabular lists in Sections II, III, and IV:

a. *Source, Maintenance and Recoverability Codes (SMR)*:

(1) Source Code, indicates the selection status and source for the listed item. Source codes are:

Code	Explanation
P	Applied to repair parts which are stocked in or supplied from DSA/GSA or Army supply system, and authorized for use at indicated maintenance categories.
M	Applied to repair parts which are not procured or stocked but are to be manufactured at indicated maintenance categories.
A	Applied to assemblies which are not procured or stocked as such but are made up two or more units, each of which carry individual stock numbers and descriptions and are procured and stocked and can be assembled by units at indicated maintenance categories.
X	Applied to parts and assemblies which are not procured or stocked, the mortality of which is normally below that of the applicable end item, and the failure of which should result in retirement of the end item from the, supply system.
X1	Applied to repair parts which are not procured or stocked, the requirement for which will be supplied by use of the next higher assembly or components.
X2	Applied to repair parts which are not stocked. The indicated maintenance category requiring such repair parts will attempt to obtain them through cannibalization; if not obtainable through cannibalization, such repair parts will be requisitioned with supporting justification through normal supply channels.
C	Applied to repair parts authorized for local procurements. If not obtainable from local procurement, such repair parts will be requisitioned through normal supply channels with a supporting statement of non-availability from local procurement.
G	Applied to major assemblies that are procured with PEMA (Procurement Equipment Missile Army) funds for initial use only to be used as

Code	Explanation
	sue only to be used as exchange assemblies at DSU and GSU maintenance level. These assemblies will not be stocked above DSU and GSU or returned to depot supply level.

Note.

Source code is not shown on common hardware items known to be readily available in Army supply channels and through local procurement.

(2) Maintenance Code, indicates the lowest category of maintenance authorized to install the listed item. The maintenance level code is:

Code.	Explanation
O	Organizational maintenance

(3) Recoverability Code, indicates whether unserviceable items should be returned for recovery or salvage. Items not coded are expendable. Recoverability codes are:

Code	Explanation
R	Applied to repair parts and assemblies which are economically repairable at DSU and GSU activities and normally are furnished by supply on an exchange basis.
T	Applied to high dollar value recoverable repair parts which are subject to special handling and are issued on an exchange basis. Such repair parts normally are repaired or overhauled at depot maintenance activities.
U	Applied to repair parts specifically selected for salvage by reclamation units because of precious metal content, critical materials, high dollar value reusable casings or castings.

(4) This column also lists, below the SMR code, an index number for each item in ascending numerical sequence, which is used to locate items in the publication when the Federal stock number and/or reference number is known.

b. Federal Stock Number: This column indicates the Federal stock number for the item.

c. Description: This column indicates the Federal item name and any additional description of the item required. A part number or other reference number is followed by the applicable five-digit Federal supply code for manufacturers in parentheses. Material required for manufacture or fabrication is identified.

d. Unit of Issue: This column indicates the unit used as a basis for issue, e.g., ea, pr, ft, yd, etc.

e. Quantity Incorporated in Unit Pack: This column indicates the actual quantity contained in the unit pack.

f. Quantity Incorporated in Unit: This column indicates the quantity of the item used in the functional group.

g. Fifteen-Day Organizational Maintenance Allowance, Column (4) of Section II and Column (7) of Section III and IV.

(1) The allowance columns are divided into four subcolumns. Indicated in each subcolumn is the quantity of items authorized for the number of equipment supported. Items authorized for use as required but not for initial stockage are identified with an asterisk in the allowance column.

(2) The quantitative allowances for organizational level of maintenance represents one initial prescribed load for a 15-day period for the number of equipments supported. Units and organizations authorized additional prescribed loads will multiply the number of prescribed loads authorized by the quantity of repair parts reflected in the appropriate density column applicable to the number of items supported to obtain the total quantity of repair parts authorized.

(3) Organizational units providing maintenance for more than 100 of these equipments shall determine the total quantity of parts required by converting the equipment quantity to a decimal factor by placing a decimal point before the next to last digit of the number to indicate hundredths, and multiplying the decimal factor by the parts quantity authorized in the 51-100 allowance column. Example, authorized allowance for 51-100 equipments is 40; for 150 equipments multiply 40 by 1.50 or 60 parts required.

(4) Subsequent changes to allowances will be limited as follows: No change in the range of items is authorized. If additional items are considered necessary, recommendation should be forwarded to U.S. Army Mobility Equipment Command for exception or