

ARMY
NAVY
AIR FORCE

TM 11-5895-856-34-10
EE640-CA-MMI-100/E154 CPU
TO 31W2-2T-122-10

TECHNICAL MANUAL

DIRECT SUPPORT AND GENERAL SUPPORT
MAINTENANCE MANUAL
FOR
CENTRAL, MESSAGE SWITCHING, AUTOMATIC
AN/TYC-39(V)1
AND
CENTRAL OFFICE, TELEPHONE, AUTOMATIC
AN/TTC-39(V)2

AUTOMATIC DATA PROCESSING
ASSEMBLIES

DEPARTMENTS OF THE ARMY, NAVY, AND AIR FORCE

22 SEPTEMBER 1983

TECHNICAL MANUAL
NO. 11-5895-856-34-10
TECHNICAL MANUAL
EE640-CA-MMI-100/E154 CPU
TECHNICAL ORDER
TO 31W2-2T-122-10

DEPARTMENTS OF THE ARMY
THE NAVY, AND
THE AIR FORCE

Washington, DC, 22 September 1983

**DIRECT SUPPORT AND GENERAL SUPPORT
MAINTENANCE MANUAL
FOR
CENTRAL, MESSAGE SWITCHING, AUTOMATIC
AN/TYC-39(V)1
AND
CENTRAL OFFICE, TELEPHONE, AUTOMATIC
AN/TTC-39(V)2**

**AUTOMATIC DATA PROCESSING
ASSEMBLIES**

REPORTING ERRORS AND RECOMMENDING IMPROVEMENTS

You can help improve this manual. If you find any mistakes or if you know of a way to improve the procedures, please let us know. Mail your letter, DA Form 2028 (Recommended Changes to Publications and Blank Forms), or DA Form 2028-2 located in back of this manual direct to: Commander, US Army Communications-Electronics Command and Fort Monmouth, ATTN: DRSEL-ME-MP, Fort Monmouth, New Jersey 07703.

For Air Force, submit AFTO Form 22 (Technical Order System Publication Improvement Report and Reply) in accordance with paragraph 6-5, Section VI, T.O. 00-5-1. Forward direct to prime ALC/MST.

For Navy, mail comments to the Commander, Naval Electronics Systems Command, ATTN: ELEX 8122, Washington, DC 20360.

In either case, a reply will be furnished direct to you.

TABLE OF CONTENTS

VOLUME 10 TM 11-5895-856-34-10

Card Cage Assembly, Interface Control Unit - R.H., Wire List, Logic (149015-860)

This volume is part of a 24-volume set covering the direct support and general support maintenance of the automatic data processing assemblies. This volume contains the logic wire list for the right-hand card cage assembly of the interface control unit, drawing number 149015-860. Refer to volume 1 of this series (TM 11-5895-856-34-1) for an explanation of how to use this wire list as well as other lists contained in the set.

NOTE

The pages in volumes 2 through 24 of TM 11-5895-856-34 have been numbered in a special manner. Pages within these volumes are found by keying to two page identifiers: the drawing number and the page number. To find the page that you desire within the volume, follow the steps listed below:

1. Find the applicable wire run list in the table of contents and note the applicable drawing number.
2. Look through the pages of the volume until you find the particular drawing number of the wire run list that you seek. This will insure that you are in the correct wire run section.
3. Go through these pages until you find the page number you are looking for within this particular wire run list.

Remember, pages in the volumes cited above are found by keying to the drawing number applicable to a particular wire run list, as well as, a page number. Make sure you are on the correct page by checking both page identifiers.

**CARD CAGE ASSEMBLY, INTERFACE CONTROL UNIT
- RIGHT HAND
LOGIC WIRE LIST
149015-860**

NOTES: UNLESS OTHERWISE SPECIFIED

1. REFERENCE TO SHEET 3 FOR DEFINITION OF FIELDS.
2. REFERENCE TO SHEET 4 FOR CONFIGURATIONS OF SHIELD AND WIRE TERMINATIONS.
3. REFERENCE TO SHEET 5 OF STRING LIST FOR WIRE CODE DEFINITIONS.
4. REFERENCE TO SHEET 6 OF STRING LIST FOR WIRE PARTS LIST.
5. ALL ABBREVIATIONS PER MIL-STD-12.
6. THROUGHOUT THE BODY OF THIS DOCUMENT THE UNIT NAME IS REFERRED TO AS: CARD CAGE ASSEMBLY IFCU.

H78 STRING AND CONNECTOR LIST, DEFINITION OF FIELDS

1. **Record Number** - A unique Data Processing number which associates all information pertaining to a wire "FROM" Connector, "TO" Connector, Wire Code, etc. This number is the wire ID when that field is blank.
2. **Prefix** - An assembly alphanumeric to be used when a wire terminates in two assemblies. This number will be the reference designation as required by USAS Y32.16-1968.
3. **Connector** - Any type of terminating point, plug, receptacle, etc. Designations are in accordance with USAS Y32.16-1968.
4. **Pin** - Exact terminating point of the respective connector. Designations are unique:
 - A. SHXXXX indicates the junction of a shield and a pigtail, the four digits to the right are the wire identity of the shielded wire.
 - B. JCT indicates a common point of two or more shield pigtails.
 - C. Jacket: the terminology used when describing the line that defines the identification of a shielded wire.
5. **Sh Fg** - References a graphic representation showing how a shielded wire or coax is to be terminated. A number in this field indicates the level of automatic wire wrapping.
6. **Multi Group** - Associates wires of a group such as "twisted wire" or "shielded wire". Jacket, pigtails and center conductors will be shown as a common group.
7. **Wire Code** - A three-digit code for wire type and gage or bus bar.
8. **Wire Color** - Standard RETMA color code.
 - A. Base Stripe Tracer.
 - B. Stripe, Tracer 1 and Tracer 2 if the digit to the left is other than 9 and the two positions to the right are not blank and not equal. The Base Color is understood to be white.
9. **Wire Ident** - A number used for reference to differentiate one wire from another. This number will be used to identify the wire when specified in the wire list sleeve code field.
10. **Spc Inst** - A code which indicates that a wire must be given special attention as follows:
 - A. Direct routing, no service loops, no harnessing.
 - B. See general notes or instruction pages.
 - C. See general notes or instruction pages.
 - D. See general notes or instruction pages.
 - E. See general notes or instruction pages.
 - F. See signal description.
 - G. This connection does not go directly to the "TO" connector, but intersects a line going to the "TO" connector.
 - H. See special routing page.
 - I. Junction point for multilayer laminated board (MLB) connection.
 - J. Denotes a bus reference point.
 - K. Blank out "TO" connector and pin.
 - L. Will cause a signal name of three characters or less to be entered in the string list.
 - M. Will cause a record to be omitted from the string list. (This record will print in the connector list.)
 - N. Will suppress printing the wire Identity in the harness string and double entry list.
 - P. Will cause the equation to be used as the signal name for sorting purposes only in the string list.


H78 STRING AND CONNECTOR LIST, DEFINITION OF FIELDS - Continued

- Q. Will cause an equation record to be omitted from logic listing.
 - R. Will suppress printing the "FROM, TO" pin number in the string and connector lists.
 - S. Do not move record number to the ident field for an ADD transaction in the harness string and double entry only. (Use only when adding a file.)
 - T. Twist wire code.
 - U. Not available.
 - V. See general notes or instruction pages.
 - W. Fixed wire length submitted.
 - X. Sequence of string ls to be left as is.
 - Y. See general notes or instruction pages.
 - Z. Will suppress printing of the 'FROM' pin.
10. **Misc** - Unless otherwise noted, the number 1 indicates a pre-wired connector.
 11. **Signal** - An alphanumeric signal name, mnemonic where feasible, which identifies one specific function from another.
 - SPP - Denotes an available termination.
 - SPF - Denotes an unwired termination which has an assigned function.
 - SPW - Denotes a non-functional wire which is terminated at one or both ends.
 - SPO - Denotes a spare output of a circuit.
 - DNW - Indicates that a termination may not be wired.
 - SPA - Denotes an unassigned circuit as one of a group on a printed circuit board.
 - SPI - Denotes a spare output of a circuit.
 - SPG - Denotes an unassigned logic gate, as one of a group on a printed circuit board.
 - SPR - Denotes a spare resistor.
 - SPD - Denotes an input diode of an assigned logic gate.
 12. **Scq No** - A number which in conjunction with SIGNAL. allows a signal string to be consistently printed in a given order..
 13. **Equation** - A mnemonic, named assigned to each gate of an element.
 14. **Term** - An "OR" function composed of one or more factors
 15. **Factor** - A specified input to a logical gate or active element.
 16. **Ckt or Chip Type** - Denotes a specific board type..
 17. **Group** - Denotes a specific circuit on a printed circuit board.
 18. **Load or Power Plane** - Denotes the current draw in milliamps by a specific circuit or voltage.
 19. **AND Test Point** - Denotes the input test point for a specific circuit on a printed circuit board.
 20. **OR Test Point** - Denotes the output test point for a specific circuit on a circuit board.
 21. **Signal Description** - A written description or name of a signal or voltage.
 22. **ECO No.** - A letter number combination to show the Engineering Change Order level of that particular wire list record.

Drawing No.
149015-860
Rev. C, sheet 3


SHIELD FIGURE A

SHIELD TERMINATION FOR SHIELDED,
SINGLE AND MULTIPLE CONDUCTORS,
NO PIGTAIL IS REQUIRED.



SHIELD FIGURE B


SHIELD TERMINATION FOR SHIELDED,
SINGLE AND MULTIPLE CONDUCTORS,
FRONT PIGTAIL IS REQUIRED.



SHIELD FIGURE NO. 3

SHIELD FIGURE NO. 2


SHIELD FIGURE NO. 1



SHIELD FIGURE NUMBER
INDICATES LEVEL OF WIRE WRAP



SHIELD FIGURE G

SHIELDED CABLE TERMINATION WITH DRAIN WIRE



SHIELD FIGURE C

SHIELD TERMINATION FOR SHIELDED,
SINGLE AND MULTIPLE CONDUCTORS,
A REAR PIGTAIL IS REQUIRED.




SHIELD FIGURE X

SHIELDED WIRE
PIGTAILS—HYBRID


SHIELD FIGURE Z

COAXIAL CONNECTOR TERMINATION




SHIELD FIGURE N

TRANSITION DEVICE WITH
SOLID WIRE PIGTAILS



SHIELD FIGURE M

TRANSITION DEVICE WITH
STRANDED WIRE PIGTAILS



**DATA SYSTEMS DIVISION
LITTON SYSTEMS INC.
LITTON INDUSTRIES**

DRAWING NUMBER **149015-860**

UNIT ASSEMBLY NAME CARD CAGE ASSEMBLY IFCU

TM 11-5895-856-34-10/EE640-CA-MMI-100/E154 CPU/TO 31W2-2T-122-10

UNIT ASSEMBLY NO. 149015 REV. C INDEX JAEBRA

FILE IDENT	T39CIFC5	DATE	09-03-82	PAGE	5
------------	----------	------	----------	------	---

[illegible]