

TECHNICAL MANUAL

OPERATOR'S, ORGANIZATIONAL, DIRECT SUPPORT, AND
GENERAL SUPPORT MAINTENANCE MANUAL
INCLUDING REPAIR PARTS AND SPECIAL TOOLS LISTS

FOR

TELEPHONE TEST OSCILLATOR TS-3329/U
(NSN 6625-00-251-5211)
(HEWLETT-PACKARD MODEL 236A)

H E A D Q U A R T E R S , D E P A R T M E N T O F T H E A R M Y

8 FEBRUARY 1980

TECHNICAL MANUAL }
No. 11-6625-2903-14&P }

HEADQUARTERS,
DEPARTMENT OF THE ARMY
WASHINGTON, DC 8 February 1980

**OPERATOR'S, ORGANIZATIONAL, DIRECT SUPPORT, AND
GENERAL SUPPORT MAINTENANCE MANUAL
INCLUDING REPAIR PARTS AND SPECIAL TOOLS LISTS
FOR
TELEPHONE TEST OSCILLATOR TS-3329/U
(NSN 6625-00-251-5211)
(HEWLETT-PACKARD MODEL 236A)**

REPORTING ERRORS AND RECOMMENDING IMPROVEMENTS

You can help improve this manual. If you find any mistakes or if you know of a way to improve the procedures, please let us know. Mail your letter or DA Form 2028 (Recommended Changes to Publications and Blank Forms), or DA Form 2028-2 located in back of the manual direct to: Commander, US Army Communications and Electronics Materiel Readiness Command, ATTN: DRSEL-ME-MQ, Fort Monmouth NJ 07703.

In either case a reply will be furnished direct to you.

This manual is an authentication of the manufacturer's commercial literature which, through usage, has been found to cover the data required to operate and maintain this equipment. Since the manual was not prepared in accordance with military specifications and AR 310-3, the format has not been structured to consider levels of maintenance.

Table of Contents

Section	Page
0. INTRODUCTION	
0-1. Scope.....	0-1
0-2. Indexes of Publications.....	0-1
0-3. Maintenance Forms, Records and Reports.....	0-1
0-4. Reporting Equipment Improvement Recommendations (EIR).....	0-1
0-5. Administrative Storage.....	0-1
0-6. Destruction of Army Electronics Materiel.....	0-1
I. GENERAL INFORMATION	
1-1. Instrument Description.....	1-1
1-5. Instrument Identification.....	1-1
1-7. Applications.....	1-1
II. INSTALLATION	2-1
2-1. Inspection.....	2-1
2-3. Power Requirements.....	2-1
2-5. Three-Conductor Power Cable.....	2-1
2-7. Battery.....	2-1
2-9. Installation and Removal of Battery.....	2-1
2-12. Repackaging for Shipment.....	2-1
III. OPERATING INSTRUCTIONS	3-1
3-1. Introduction.....	3-1
3-3. Description of Front Panel Controls.....	3-1
3-5. Calibration.....	3-1
3-7. Operating Procedure.....	3-1
3-9. Applications.....	3-1
IV. FUNCTIONING OF EQUIPMENT	4-1
4-1. Introduction.....	4-1
4-3. Circuit Description.....	4-1
4-4. Oscillator.....	4-1
4-8. Impedance Converter.....	4-1
4-10. Amplifier.....	4-1
4-13. Peak Detector.....	4-2

<i>Section</i>		<i>Page</i>
4-15.	Output Attenuator	4-2
4-17.	Power Source	4-2
4-22.	AC Power Source	4-2
4-24.	Meter Circuit	4-2
4-26.	Regulated Power Supply	4-2
4-29.	Output Circuitry	4-2
V.	MAINTENANCE	5-1
5-1.	Introduction	5-1
5-3.	Test Equipment Required	5-1
5-5.	Cabinet Removal	5-1
5-7.	Performance Checks	5-1
5-10.	Frequency Dial Accuracy Check	5-2
5-11.	Frequency Response Check	5-2
5-12.	Distortion Check	5-3
5-13.	Spurious Oscillations Check	5-3
5-14.	Output Impedance Check	5-3
5-15.	Holding Coil Resistance Check	5-4
5-16.	Meter Check	5-4
5-17.	Attenuator Accuracy Check	5-5
5-18.	Output Impedance Phase Angle Check	5-5
5-19.	Output Balance Check	5-5
5-20.	Output Hum and Noise Check	5-5
5-21.	Adjustment Calibration Procedures	5-6
5-24.	Meter Mechanical Zero Set	5-6
5-26.	Power Supply Adjustment	5-6
5-32.	Frequency Calibration	5-7
5-33.	Minimum Distortion Adjustment	5-7
5-34.	Feedback Adjustment	5-8
5-35.	Output Calibration Adjustment	5-8
5-36.	Troubleshooting Techniques	5-8
5-40.	Servicing Etched Circuit Board	5-8
VI.	REPLACEABLE PARTS	6-1
6-1.	Introduction	6-1
6-4.	Ordering Information	6-1
6-6.	Non-Listed Parts	6-1
APPENDICES		
A.	Difference Data Sheets	A-1
B.	References	B-1
C.	Maintenance Allocation	C-1

List of Illustrations

<i>Figure</i>		<i>Page</i>
3-1.	Front Panel and Left Side Control Description	3-2
3-2.	Operation	3-3/3-4
4-1.	RC Network Characteristics	4-1
4-2.	Model 236A Block Diagram	4-3/4-4
5-1.	Frequency Dial Accuracy Check	5-2
5-2.	Frequency Response Check	5-3
5-3.	Battery Cable Connections	5-4
5-4.	Attenuator Accuracy Check	5-4
5-5.	Output Balance Check	5-6
5-6.	A1 Component Location	5-11
5-7.	A2 Component Location	5-11
5-8.	Model 236A Schematic Diagram	5-12
5-9.	Model 236A Attenuator Schematic	5-13/5-14

List of Tables

<i>Table</i>		<i>Page</i>
1-1.	Specifications	1-1
1-2.	General Information	1-1
2-1.	Suitable Batteries	2-1
5-1.	Test Equipment Required	5-0
5-2.	Output Hum and Noise Check	5-6
5-3.	Troubleshooting from Front Panel Symptoms	5-9
5-4.	Isolating Malfunctions	5-10
6-1.	Replaceable Parts	6-2
6-2.	Part Number-National Stock Number Cross Reference Index	6-7

SECTION 0 INTRODUCTION

0-1. Scope

This manual applies to HP Model 236A, telephone test oscillator, Serial Numbers: 1107A6774 and greater. See Appendix A to adapt manual to earlier serial numbers. The equipment will be referred to as the Oscillator throughout the manual.

0-2. Indexes of Publications

a. DA Pam 310-4. Refer to the latest issue of DA Pam 310-4 to determine whether there are new editions, changes, or additional publications pertaining to the equipment.

b. DA Pam 310-7. Refer to DA Pam 310-7 to determine whether there are modification work orders (MWO's) pertaining to the equipment.

0-3. Maintenance Forms, Records and Reports

a. Report of Maintenance and Unsatisfactory Equipment. Department of the Army forms and procedures used for equipment maintenance will be those prescribed by TM 38-750, the Army Maintenance Management System.

b. Report of Packaging and Handling Deficiencies. Fill out and forward DD Form 6 (Packaging Improvement Report) as prescribed in AR 700-58/NAVSUPINST/4030.29/AFR 71-12/MCO P4030.29A, and DLAR4145.8.

c. Discrepancy in Shipment Report (DISREP) (SF361). Fill out and forward Discrepancy in Shipment Report (DISREP) (SF 361) as prescribed in AR 55-38/NAVSUPINST 4610.33B/AFR 75-18/MCOP4610.19C and DLAR 4500.15.

0-4. Reporting Equipment Improvement Recommendations (EIR)

If your TS-3329/U needs improvement, let us know. Send us an EIR. You, the user, are the only one who can tell us what you don't like about your equipment. Let us know why you don't like the design. Tell us why a procedure is hard to perform. Put it on an SF 368 (Quality Deficiency Report). Mail it to us at Commander, US Army Communications and Electronics Materiel Readiness Command, ATTN: DRSEL-ME-MQ, Fort Monmouth, NJ 07703. A reply will be furnished to you

0-5. Administrative Storage

Administrative storage of equipment issued to and used by Army activities shall be in accordance with TM 740-90-1.

0-6. Destruction of Army Electronics Materiel

Destruction of Army Electronics materiel to prevent enemy use shall be in accordance with TM 750-244-2.