

PUMPING ASSEMBLY, DIESEL ENGINE DRIVEN,
WHEEL MTD, 600 GPM, 150 PSI HEAD
NSN 4320-01-314-8844
References: TM 10-4320-315-10 and TM 10-4320-315-24
Federal Supply Catalog C91 00-IL

REPORTING OF ERRORS

You can improve this publication by calling attention to errors and by recommending improvements and by stating your reasons for the recommendations. Your letter or DA form 2028, Recommended Changes to Publications and Forms, should be mailed directly to Commander, U.S. Army Aviation and Troop Command, ATTN: AMSAT-I-MTS, 4300 Goodfellow Blvd., St. Louis, MO 63120-1798

Level of maintenance. The lowest level of maintenance authorized to lubricate a point is indicated by one of the following symbols as appropriate: operator/Crew (C); and Unit Maintenance (O).

Intervals and the related man hour times are based on normal operation. The manhour time specified is the time you need to do all the services prescribed for a particular interval. Change the Interval if your lubricants are contaminated or if you are operating the equipment under adverse operating conditions, including longer than usual operating hours. You may extend the interval during periods of low activity, but you must take adequate preservation precautions.

Hard time oil change intervals are applied. The Army Oil Analysis Program (AOAP) LABORATORY support is not available at this time.

CAUTION - Ensure pumping assembly is level before checking oil levels.

WARNING - Dry cleaning solvent, PD680, used to clean parts is potentially dangerous to personnel and property. Avoid repeated or skin contact. Do not us near open flame or excessive heat. Flash point of solvent is 100 - 138° F (38 -60°C). Lubricate immediately after fording, or m soon after as unit movement permits.

Clean fittings before lubricating. Clean parts with solvent, dry cleaning PD-680 or an approved solvent. Dry fitting before lubricating.

DISTRIBUTION STATEMENT A - Approved for public release; distribution is unlimited.

