

23 May 1978 (Supersedes LO 5-4320-222 15, 12 October 1961)

PUMP, RECIPROCATING: DIAPHRAGM; GASOLINE DRIVEN;
WHEEL MOUNTED, RUBBER TIRES; 4 IN. 100 GPM AT 10
FT. SUCTION LIFT (RICE PUMP AND MACHINE CO
MODEL 4D-327) W/MILITARY STANDARD
ENGINE MODEL 2A016-2

Reference LO 5-2805-257 12 and C9100-1L

Intervals and related task-hour times are based on normal hours of operation. The task hour time specified is the time you need to do all the services prescribed for a particular interval. Change the Interval If your lubricants are contaminated or if you are operating the equipment under adverse operating conditions, including longer-than-usual operating hours. You may extend the Interval during periods of low activity, but you must take adequate preservation precautions.

The time specified is the time required to perform all services at the particular Interval.

Clean fittings before lubricating. Relubricate all areas exposed to water after amphibious operation Lubricate points.

indicated by dotted arrow shaft on both sides of equipment Clean parts with SOLVENT, dry cleaning, or with OIL, fuel, diesel Dry before lubricating Drain crankcase when HOT Fill and check level. The lowest level of maintenance authorized to lubricate a point is indicated by one of the following (C) Operator/crew, or 1O) Organizational Maintenance.

You can help improve this publication. If you find any mistake or If you know of a way to improve the procedures, please let us know. Your letter or DA Form 2028 (Recommended Changes to Publications and Blank Forms) should be mailed directly to Commander, U S Army Troop Support & Aviation Materiel Readiness Command, ATTN DRSTS-MTPS, 4300 Goodfellow Blvd St Louis, MO 63120 A reply will be furnished to you.

TOTAL TASK-HR		TOTAL TASK-HR	
INTERVAL	TASK-HR	INTERVAL	TASK-HR
10	02	250	03

FOLD

FOLD

