

23 May 1978 (Supersedes LO F432234 12, 14 March 1976)

PUMP, CENTRIFUGAL, SELF-PRIMING, GASOLINE ENGINE DRIVEN,
WHEEL MOUNTED, 6-INCH, 1500 GPM CAPACITY AT 60 FOOT
HEAD (PEABODY BARNES MODEL US90CCG-1) W/ENGINE
CONTINENTAL MODEL FS244-6100P

Reference: C9100-IL

Intervals and related task-hour timer are based on normal hours of operation. The task-hour time specified is the time you need to do all the services prescribed for 1 particular interval. Change the interval if your lubricants re contaminated or if you are operating the equipment under adverse operating condition, including longer-than usual operating hours. You may extend the interval during periods of low activity, but you must take adequate preservation precautions.

*The time specified is the time required to perform all services at the particular interval.

Clean fittings before lubricating. Relubricate all arm ex-pose to water after amphibious operation. Lubricate points indicated by dotted arrow shaft on both side of equipment

Clean part with SOLVENT, dry cleaning, or with OIL, fuel, diesel. Dry before lubricating. Drain crankcase when HOT. Fill end check level. The lowest level of maintenance authorized to lubricate a point is indicated by one of the following: (C) Operator/crew; or (O) Organizational Maintenance.

You can help improve this publication. If you find any mistake or if you know of a way to improve the procedures, people let us know. Your letter or DA Form 2028 (Recommended Changes to Publication and Blank Form) should be mailed directly to: Command, U.S. Army Troop Support & Aviation Materiel Readiness Command, ATTN: DRSTS-MTPS, 4300 Goodfellow Blvd. St. Louis, MO G3120. A reply will be furnished to you.

*TOTAL TASK-HR		*TOTAL TASK-HR	
INTERVAL	TASK-HR	INTERVAL	TASK-HR
10	0.1	150	0.5
50	0.3	2000	2.0

FOLD

FOLD

