

DEPARTMENT OF THE ARMY TECHNICAL BULLETIN

HOISTING UNIT TRUCK MOUNTING:
ORGANIZATIONAL MAINTENANCE, SET NO. 7
(4910-754-0652)

INSTALLATION IN ONE 2-1 / 2-TON,
6X6 CARGO TRUCK, M34 OR M35

Headquarters, Department of the Army, Washington, D.C.
 27 November 1970

This bulletin is current to 7 October 1970.

1. General a. Instructions contained in this bulletin are to be used as a guide for installation of Hoisting Unit Truck Mounting, Organizational Maintenance, Set No. 7, 4910-754-0652, in one 2½ - Ton, 6 x 6 Cargo Truck, M34 or M35.

b. These instructions are to be followed as prescribed in most instances. However, slight variations to the installation may be made at the discretion of the Officer in charge.

c. A complete list of items contained in this set is included in SC 4910-95-CL-A51.

d. Precautions should be observed when drilling holes through the body to insure the waterproof

characteristics of the body are retained. All hardware extending through the floor of the truck should have outer parts covered with undercoating similar to that used on the underside of vehicles. Care should be taken that holes drilled into the floor do not penetrate the frame or cross members of the vehicle.

2. Installation of Hoisting Unit. a. The floor plan for the truck with each item in its designated spot is shown in figure 1. Right-side view of superstructure is shown in figure 2. Superstructure, Hoist is shown in figure 3. Items to be mounted are listed in table 1.

Table 1. Items to be Mounted

FSN	Item Name	Qty	Fig. no.	Item ident.
3950-343-9966	SUPERSTRUCTURE, HOIST:	1	1, 2 and 3	1
3950-223-3396	HOIST, CHAIN:	1	1 and 2	2
4910-735-6056	TOWBAR, MOTOR VEHICLE:	1	1	3

* This technical bulletin supersedes TB ORD 444-3, dtd 9 June 1952.