

DEPARTMENT OF THE ARMY TECHNICAL BULLETIN
CALIBRATION PROCEDURE FOR
NAVIGATIONAL CONTROL SIMULATOR
SM-254/ASM
(NSN 6930-00-863-3399)

Headquarters, Department of the Army, Washington, DC
27 February 1978

REPORTING OF ERRORS

You can help improve this publication by calling attention to errors and by recommending improvements and stating your reasons for the recommendations. Your letter of DA Form 2028 (Recommended Changes to Publications and Blank Forms) should be mailed direct to Commander, US Army Electronics Command, ATTN: DRSEL-MA-Q, Fort Monmouth, NJ 07703. A reply will be furnished direct to you

	Paragraph	Page
Section I. IDENTIFICATION AND DESCRIPTION		
Test instrument identification	1	1
Calibration data card (DA Form 2416)	2	1
Calibration description	3	1
II. EQUIPMENT REQUIREMENTS		
Equipment required	4	2
Accessories required	5	2
III. CALIBRATION PROCESS		
Preliminary procedure	6	2
Synchro transmitter	7	3
Final procedure	8	3

Section I. IDENTIFICATION AND DESCRIPTION

- 1. Test Instrument Identification** a. This bulletin provides instructions for the calibration of Navigational Control Simulator SM-254/ASM. The simulator being calibrated will be referred to as the Test Instrument throughout this procedure.
- b. The time required to perform this calibration is approximately 1 hour.
- 2. Calibration Data Card (DA Form 2416)** a. Forms, records, and reports required for calibration personnel at all levels are prescribed by TM 38-750. DA Form 2416 must be annotated in accordance with TM 38-750 for each calibration performed.
- b. Adjustments to be reported on DA Form 2416 are designated (R) at the end of the sentence in which they appear. When adjustments are in tables, the (R) follows the designated adjustment. Report only those adjustments made and designated with (R).
- 3. Calibration Description** Test Instrument parameters and performance specifications which pertain to this calibration are listed in table 1.

*This bulletin supersedes TB 11-6625-481-45/1, 27 July 1967.