

LUBRICATION ORDER-52

6 AUGUST 1985-.N ,

CLOTHING REPAIR SHOP, TRAILER MOUNTED MODEL: CRS

NSN: 3530-01-133-3494

CLOTHING SEWING MACHINE CHANDLER MODEL NO. C765

Reference TM10-3530-205-14 and C9100-IL

Intervals (on-condition or hard time) and the related task-hour times are based on normal operation. The task-hour time specified is the time you need to do all the services prescribed for a particular interval. On-condition (OC) oil sample intervals shall be applied unless changed by Army Oil Analysis Program (AOAP) laboratory. Change the hard time interval if your lubricants are contaminated or if you are operating the equipment under adverse operating conditions including longer-than-usual operating hours. The hard time interval may be extended during periods of low activity. If extended adequate preservation precautions must be taken. Hard time intervals will be applied in the event AOAP laboratory support is not available.

Clean all lubrication points with dry cleaning solvent (SD), type II or equivalent. Dry before lubricating. The lowest level of maintenance to lubricate a point is indicated by one of the following:

(C) Operator/Crew or (OO) Organizational Maintenance.

You can help improve this manual. If you find any mistakes or if you know of a way to improve procedures, please let us know. Mail your letter or DA Form 2028 (Recommended Changes to Publications and Blank Forms) direct to: Commander, US Army Troop Support Command, ATTN: AMSTR-MPS, 4300 Goodfellow Blvd, St. Louis, MO 63120-1798. A reply will be furnished to you.

