

LUBRICATION ORDER

L05-2330-305-12

13 MAY 1985

(Supersedes LO 5-2330-305-12, 7 September 1983)

TOPOGRAPHIC SUPPORT SYSTEM**CHASSIS, SEMI-TRAILER****NSN: 233041-076-4797**

Reference TM 5-2330.305.14

Intervals (on-condition or hard time) and the related task-hour times are based on normal operation. * The task-hour time specified is the time you need to do all the services inscribed for a particular interval, On-condition (OC) oil sample intervals shall be applied unless changed by the Army Oil Analysis Program (AOAP) laboratory. Change the hard time interval if your lubricants are contaminated or if you are operating the equipment under adverse operating conditions, including longer-than-usual operating hours. The hard time interval may be extended

during periods of low activity. If extended, adequate preservation precautions must be taken. Hard time intervals will be applied in the event AOAP laboratory support is not available. Clean fittings before lubricating. Clean ports with dry cleaning solvent (SD), type II or equivalent. Dry before lubricating. Dotted arrow points indicate lubrication on both sides of the equipment. The lowest level of maintenance authorized to lubricate a point is indicated by one of the following symbols as appropriate: Operator/Crew (C), and Organizational Maintenance (O).

LUBRICANT • INTERVAL**INTERVAL • LUBRICANT**