

LUBRICATION

ORDER

16 JANUARY 1974 (Supersedes LO 5-3895-339-12, Dated 4 MAY 73)

KETTLE, HEATING, BITUMINOUS: G.E.D., TRAILER MOUNTED,
165 GAL. CAPACITY (GENERAL STEEL TANK MODEL 1901)

FSN 3895-351-2354

Reference: LO 5-2805-256-12 and FEDERAL SUPPLY CATALOG C9100-IL

Intervals are based on normal hours of operations. Adjust to compensate for abnormal operations and severe conditions. During inactive periods, sufficient lubrication must be performed for adequate preservation.

Clean fittings before lubricating.

Relubricate after washing.

Clean parts with SOLVENT, dry-cleaning, Type 11 (SD-2). Dry before lubricating.

Lubricate points indicated by dotted arrow shafts on both sides of equipment.

Drain gearcases when hot. Fill and check level.

*The time specified is the time required to perform all services at the particular interval.

*TOTAL MAN-HR		*TOTAL MAN-HR	
INTERVAL	MAN-HR	INTERVAL	MAN-HR
10	0.2	250	0.4
50	0.4	500	0.2
100	0.1	1000	1.0

FOLD

FOLD

LUBRICANT ● INTERVAL

INTERVAL ● LUBRICANT

For Engine Lubrication
See LO5-2805-256-12

